

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 6
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	6	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	5,8	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	5,826	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,6	%
Other items			
Standby heat loss	$P_{stby}$	0,076	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 9
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	9	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	8,7	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	8,736	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,6	%
Other items			
Standby heat loss	$P_{stby}$	0,076	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 12
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	12	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	11,6	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	11,646	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,6	%
Other items			
Standby heat loss	$P_{stby}$	0,076	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 14
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	14	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	13,6	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	13,586	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,8	%
Other items			
Standby heat loss	$P_{stby}$	0,076	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 16
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	16	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	15,5	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	15,526	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,7	%
Other items			
Standby heat loss	$P_{stby}$	0,076	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 18
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	18	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	17,5	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	17,466	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,9	%
Other items			
Standby heat loss	$P_{stby}$	0,095	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 20
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	19	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	19,4	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	19,406	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,8	%
Other items			
Standby heat loss	$P_{stby}$	0,095	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 22
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	21	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	21,3	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	21,346	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,7	%
Other items			
Standby heat loss	$P_{stby}$	0,095	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).



Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 24
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	23	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	23,3	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	23,286	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,8	%
Other items			
Standby heat loss	$P_{stby}$	0,095	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 28
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	27	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	27,2	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	27,166	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,8	%
Other items			
Standby heat loss	$P_{stby}$	0,113	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 32
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	31	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	31	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	31,046	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,7	%
Other items			
Standby heat loss	$P_{stby}$	0,113	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 36
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	35	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	34,9	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	34,926	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,8	%
Other items			
Standby heat loss	$P_{stby}$	0,113	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 40
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	39	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	38,8	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	38,806	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,8	%
Other items			
Standby heat loss	$P_{stby}$	0,113	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 44
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	43	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	42,7	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	42,686	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,8	%
Other items			
Standby heat loss	$P_{stby}$	0,113	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details: Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 48
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	47	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	46,6	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	46,566	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,8	%
Other items			
Standby heat loss	$P_{stby}$	0,113	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 52
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	50	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	50,4	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	50,446	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,8	%
Other items			
Standby heat loss	$P_{stby}$	0,113	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).



Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 56
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	54	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	54,3	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	54,326	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,8	%
Other items			
Standby heat loss	$P_{stby}$	0,113	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 60
Condensing boiler	NO
Low-temperature (**) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	58	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	58,2	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	58,206	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,8	%
Other items			
Standby heat loss	$P_{stby}$	0,113	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).

Information requirements for boiler space heaters according to Commission regulation (EU) No 813/2013

Manufacturer/ trademark	Termostroj
Model	Termo-Extra 64
Condensing boiler	NO
Low-temperature (***) boiler	NO
B1 boiler	NO
Cogeneration space heater:	NO
Combination heater:	NO

Item	Symbol	Value	Unit
<b>Rated heat output</b>	Prated	62	kW
For boiler space heaters and boiler combination heaters: Useful heat output			
At rated heat output and high-temperature regime (*)	$P_4$	62,1	kW
Auxiliary electricity consumption			
At full load	$el_{max}$	62,086	kW
In standby mode	$P_{SB}$	0,006	kW
<b>Declared load profile</b>			
Daily electricity consumption	$Q_{elec}$		kWh

Item	Symbol	Value	Unit
<b>Seasonal space heating energy efficiency</b>	$\eta_s$	36	%
For boiler space heaters and boiler combination heaters: Useful efficiency			
At rated heat output and high-temperature regime (*)	$\eta_4$	38,8	%
Other items			
Standby heat loss	$P_{stby}$	0,113	kW
<b>Water heating energy efficiency</b>	$\eta_{wh}$		%
Daily fuel consumption	$Q_{fuel}$		kWh

Contact details Termostroj d.o.o., Franje Puškarića 1d, 10250 Lučko, Croatia

(\*) High-temperature regime means 60 °C return temperature at heater inlet and 80 °C feed temperature at heater outlet.

(\*\*) Low temperature means for condensing boilers 30 °C, for low-temperature boilers 37 °C and for other heaters 50 °C return temperature (at heater inlet).